

Europa Series - High Speed Printers

The best just got better



- Crisp 450 ppi resolution - HD Prints™
- LED/LCD technology
- 5+ year lamphouse life
- Thermal Backprinter, 68 character
- PdfDF 4.2 enabled
- Standard take-up and supply cassettes



In partnership with



Next generation solutions to energize your business.

Europa Series

High Speed Digital RA4 Printer Specification

| | |
|------------------------|---|
| Image Format (Input) | JPEG, TIFF, BMP. Other print formats are also supported from industry standard devices with output in L*a*b color space |
| Image Sources | PfDF server, BMC, storage server, eGate or other 3rd party systems |
| Throughput Speed | 5,000, 10,000, or 15,000 prints per hour (excluding paper changes) depending on model |
| Output Options | 3.5 in, or 7.6 cm roll-to-roll RA4 paper of any length 4 in, or 10.2 cm roll-to-roll RA4 paper of any length 4.5 in, or 11.4 cm roll-to-roll RA4 paper of any length 5 in, or 12.7 cm roll-to-roll RA4 paper of any length |
| Output Lengths | Up to 8 in, or 20.3 cm |
| Print Channel Modes | Standard print sizes, Index prints, Postcard, Wallets, Panoramic, Bordered and Custom Designs |
| Software Integration | PfDF 4.2 compatible for centralized workflow integration, XML workflow files or hot folder input |
| Backprinter | 68 character roll-to-roll thermal backprinter supporting 1 km and 2 km roll lengths. 2 lines, 34 characters/line |
| Color Management | Gretag MacBeth Eye-One™ sensitometer integrated into the system for creating color profiles |
| Resolution | 450 ppi on 3.5 inch, 4 inch and 5 inch widths |
| Exposure Technology | 2,376 LED array backlighting a high-quality LCD with a 50,000 hour lamphouse life, direct to paper exposure (no position shifting) |
| Paper Supply Cassettes | Compatible with industry-standard 1,804 ft (550 m) Agfa and/or Gretag cassettes |
| Order Control | IPSEC binary codes via punch marks for order control. Backprint barcode. PfDF datablocks for order/product assignment |
| Network Interface | Gigabit Ethernet |

Hardware Specifications

| | |
|---------------|--|
| Power Supply | 230 ± 10% 50/60Hz, 1.5k VA peak |
| Dimensions | 104.6 in x 43.4 in x 74.8 in (l x w x h) 266 cm x 110 cm x 190 cm (l x w x h) |
| Weight | 705 lbs, or 320 kg |
| Environmental | 63° to 76° F room temperature (+17° to 25° C) |

Models* upgrades available, when you need it.

| | |
|------------|--|
| Europa 5* | 5,000 prints/hour, backprinter optional |
| Europa 10* | 10,000 prints/hour, backprinter included |
| Europa 15 | 15,000 prints/hour, backprinter included |

For more information visit online www.express-imaging.com

Keith Miller, Express Imaging Systems, sales@express-imaging.com, or call 206-720-1798 ext 115

European Inquires: Derek Fieldhouse, The PhotoIntel Group, sales@photointelgroup.com, or call 44 116 2325169